



**BRICKING  
SOLUTIONS**  
A DIVISION OF **BROKK**

## HEAVY DUTY SHOCK ABSORBED SAFETY INSPECTION CAGE 2 MAN AND 4 MAN



*Safe, Portable and Easy set up*

1144 VILLAGE WAY | MONROE, WASHINGTON 98272 | USA  
800.621.7856 | 360.794.1277 | FAX 360.805.2521  
INFO@BRICKINGSOLUTIONS.COM | WWW.BRICKINGSOLUTIONS.COM

# SAFETY INSPECTION CAGE

## FEATURES & BENEFITS



1.5M (5 feet) of **portable protection** designed & certified by a professional engineer. Rated for 114kg (**250lbs**) dropped from 60 cm (24 in) with a **3:1 safety factor**. A shock absorbed panel increases safety.



Fabricated from **6061 T6 aluminum** with a steel mesh cover secured with wing nuts. Protruding bolts on top of frame hold the wire mesh in place. Rounded top adds more head room.



All sides are **color coded** for easy assembly. Adjustable height with **4 independently adjustable legs** for the varying surfaces and thickness of a coated



Easily carried by 2 people using flip-up handles attached to a safety gate. **Shoulder harness** is standard for increased stability.



On request, unassembled pieces can fit in most openings. Assembled in 15 minutes and **stores on a pallet.**

	Min Coating ID	Max Coating ID	Width	Approx Weight
<b>2 MAN CAGE</b>	2.7M	3.5M	1.5M (5ft)	100 - 114 kg (220 - 250 lbs)
<b>4 MAN CAGE</b>	3.6M	4.3M	1.5M (5ft)	295 kg (650 lbs)
Clearance cage to coating: min .30M (12 in), max .6M (24 in)			Minimum clearance head to cage: .28M (18 inches)	
Vehicle required to install cages where coating ID is above 4.3M				
<b>Cage Panel Dims any combo</b>	61 cm (24 in)	76 cm (30 in)	91 cm (36 in)	99 cm (39 in) 107 cm (42 in)

OUR SAFETY / INSPECTION CAGES ARE DESIGNED TO PROTECT YOUR WORKERS FROM FALLING COATING / BRICK UP TO 114 kg (250 lbs) FROM 60 cm (24 in) WITH A 3:1 SAFETY FACTOR. OUR CAGES ARE NOT DESIGNED NOR WILL THEY PROTECT YOU FROM MOLTEN COATING, HEAT, OR TOXIC FUMES, ETC.